

LIBRARY OF VELOCITY DEPENDENT EXTENDED SPREAD-SPECTRUM CODES

ABSTRACT

5

10

A method and apparatus is provided for determining a propagation time delay. The apparatus includes at least one source adapted to generate a plurality of positioning signals, at least one receiver deployed along a seismic sensing cable, wherein the receiver is adapted to receive the plurality of positioning signals from the at least one source, and a plurality of computed Doppler-shifted positioning signals corresponding to the plurality of positioning signals. The apparatus also includes a signal processing unit adapted to determine a propagation time delay between the source and the receiver using the generated positioning signals, the received positioning signals, and the plurality of computed Doppler shifted positioning signals.

15

[Figure 2A]

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 June 2004 (24.06.2004)


PCT

(10) International Publication Number
WO 2004/053527 A1

- (51) International Patent Classification⁷: **G01V 1/38**
- (21) International Application Number:
PCT/EP2003/050927
- (22) International Filing Date: 2 December 2003 (02.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0228484.2 6 December 2002 (06.12.2002) GB
- (71) Applicant (for AE, AG, AL, AM, AT, AU, AZ, BA, BB, BE, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CY, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GR, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, SZ, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW only): **WESTERNGECO SEISMIC HOLDINGS LIMITED** [GB/GB]; Citco Building, PO Box 662, Roadtown, Tortola (VG).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **IRANPOUR, Kambiz** [NO/NO]; Agmund Bolts Vei 46, N-0664 Oslo (NO).
- (74) Agent: **SUCKLING, Andrew**; Marks & Clerk, 4220 Nash Court, Oxford Business Park South, Oxford OX4 2RU (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (for FR only): **SERVICES PETROLIERS SCHLUMBERGER** [FR/FR]; 42, rue Saint Dominique, F-75007 Paris (FR).
- Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: LIBRARY OF VELOCITY DEPENDENT EXTENDED SPREAD-SPECTRUM CODES



(57) Abstract: A method and apparatus is provided for determining a propagation time delay. The apparatus includes at least one source (110) adapted to generate a plurality of positioning signals (130), at least one receiver (125) deployed along a seismic sensing cable (115), wherein the receiver (125) is adapted to receive the plurality of positioning signals (130) from the at least one source (110), and a plurality of computed Doppler-shifted positioning signals corresponding to the plurality of positioning signals (130). The apparatus also includes a signal processing unit adapted to determine a propagation time delay between the source (110) and the receiver (125) using the generated positioning signals (130), the received positioning signals, and the plurality of computed Doppler-shifted positioning signals.

WO 2004/053527 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.